

ORDERING CODES V926

VALVE CODES	P	V	.96H	1	D	15	.X.
Actuator type (1)							
Pneumatic actuator	P						
Electric actuator	E						
Group designation							
Globe valve, two way		V					
Valve model							
V926H – Hygienic two way angle valve			.96H				
V926A – Aseptic two way angle valve			.96A				
Valve plug							
EQP (equal percentage) – Soft (High performance EPDM)				1			
EQP (equal percentage) – Metal (AISI 316L / 1.4404)				3			
PL (linear) – Soft (High performance EPDM)				6			
PL (linear) – Metal (AISI 316L / 1.4404)				7			
PT (on-off) – Soft (High performance EPDM) – V928A only				9			
PT (on-off) – Metal (AISI 316L / 1.4404) – V928A only				10			
Pipe connection							
Tri-clamp ferrules ASME BPE					D		
Tube weld ASME BPE					DI		
Size							
1/2"						15	
3/4"						20	
1"						25	
...							
Actuator							(1)
Extras (3)							E

ACTUATOR CODES	P.	5	R	P	30
Group designation					
Multi-spring, pneumatic linear actuator	P.				
Actuator size					
205		1			
280		3			
340A – From DN 15 to DN 50		5			
340B – From DN 65 to DN 100		6			
435A – From DN 15 to DN 50		7			
435B – From DN 65 to DN 100		8			
Actuator type					
Direct action (air to close)			D		
Reverse action (air to open)			R		
Actuator Construction					
Steel construction (painted) – ADCAPure range				P	
Stainless steel construction – ADCAPure range				H	
Control signal					
0,4 – 1,2 bar (6-18 psi)					18
0,4 – 2 bar (6-30 psi)					30
0,4 – 2,4 bar (6-35 psi)					35

→ To be introduced on ".X.", if supplied in combination with the valve.

Example:

PV926H two way angle valve DN 50, tri-clamp ASME BPE complete with reverse action actuator signal 0,4 – 1,2 bar, size 340A steel:

Code: PV.96H1D50.5RP30

REMARKS:

(1) – Indicate actuator type.

(3) – To be used only when a non-standard combination valve is supplied.

Adcapture control valves are identified by a serial number on a nameplate, located on the valve and/or actuator yoke.

When ordering spares, always use that serial number. If the valve has non-standard extras the serial number also has an E (extras).