

PRESSURE GAUGES **MAN-40**

DESCRIPTION

The MAN-40 are reliable and cost-effective, general purpose bourdon tube pressure gauges designed for pressure measurement of liquid and gaseous media. They have a nominal size diameter of 40mm, units marked in bar, steel case and polycarbonate window screen.

MAIN FEATURES

USE:

AVAILABLE MODELS:

CONNECTIONS:

MEASURING RANGES:

Accuracy: 1,6% of full scale value. Designed according to EN 837-1. Backside centric connection.

OPTIONS:	Bottom radial connection.
	Complete stainless steel construction.

MAN-40.

Non-viscous and non-crystallizing liquids and

gases compatible with copper alloy.


0 - 16 bar; 0 - 25 bar; 0 - 40 bar.




ISO 228 G 1/4".	LIMITING CONDITIONS		
	Maximum allowable pressure	Full scale reading	
0 – 2,5 bar; 0 – 4 bar; 0 – 6 bar; 0 – 10 bar;	Maximum operating temperature	60 °C	
5 - 2,5 - 5 - 6, 5 - 7 - 10 - 10 - 10 - 10 - 10 - 10 - 10			

LIMITING CONDITIONS			
Maximum allowable pressure	Full scale reading		
Maximum operating temperature	60 °C		
Ambient temperature	-10 °C to 60 °C		







DIMENSIONS (mm)						
SIZE	ØA	в	с	D	sw	WGT. (kg)
DN 40	40	47	1/4"	26	14	0,07

MATERIALS				
POS. Nº	DESIGNATION	MATERIAL		
1	Case	Black steel		
2	Window	Polycarbonate		
3	Dial	White aluminium		
4	Pointer	Black aluminium		
5	Connection	Brass		
5.1	Measuring system	Copper alloy		

VALSTEAM ADCA